

Integral Tape Roofing Installation Instructions

The underlay can be used in both ventilated and non-ventilated cold & warm pitched roof systems for tiles and slates. In mainland UK and Northern Ireland the underlay should be installed in accordance with the relevant Agrément Certification as identified on the roll insert. For general information please see details below.

Non Ventilated Roofs

In non ventilated cold roof constructions, tiling battens at least 25mm thick must be used to ensure an adequate airspace between the roof covering and the underlay to allow water vapour to disperse above the underlay. If an airtight tiling system is used in combination with the underlay and the loft is unventilated, counter battens and batten space ventilators must be installed. In non ventilated cold roofs it is essential to maintain a convection tight ceiling. For additional protection the use of a vapour control layer, vapour check plasterboard should be considered.

Warm Roofs

If a vapour permeable underlay is used in a warm roof there must be an adequate flow of air through the batten space. If airtight roof tiles are used, batten space ventilators must be installed. Where the underlay is fully supported, e.g. on the insulation, counter battens will be needed to provide a ventilation void. (Counter battens are required in all warm roofs in Republic of Ireland.)

General Installation Information

Unroll the underlay exactly as indicated in Figure 1, such that the inner surface of the roll is facing uppermost and the adhesive tape strip (indicted by a red line on figure 1) is towards the ridge. Where the underlay is unsupported, ensure there is sufficient drape to allow moisture and air movement. Where the underlay is required to be draped this should be 10mm. The underlay is unrolled horizontally across the roof starting at the eaves. Subsequent rows of underlay should be lapped over the underlying row to shed water out and down the slope. Sufficient overlap should also be allowed - see table and Figure 3 below for overlap requirements. Once the overlaying underlay is in position the protective covering over the tape strip should be removed and the two layers of underlay brought together. Compression of the tape between the two layers may be assisted by having a colleague providing some resistance behind the underlay, from within the roof space. Tiling battens, centred over the overlap, and where appropriate counter battens, should be fixed over the underlay ensuring that any drape is maintained.

Installation in low external temperatures: with lower external temperatures, typically below 10°C, additional pressure may be required to ensure effective adhesion. The product should not be installed where the external temperature is below 5°C, particularly where the surface of the membrane is moist or icy. Once effectively bonded, low temperatures do not affect tape adhesion.

Alternatively, where taping of overlaps is not required, the installation instructions are identical to those above, except that the protective covering over the tape strip should not be removed.

Where softwood boarding or timber sheeting is used below the underlay, counter battens are typically required to provide effective drainage below the battens. Where timber counter battens are positioned above the underlay, there is no need to tape overlaps to resist wind uplift.

Minimum Overlaps

Roof Pitch°	Head Lap (mm)		Vertical Lap Limit (mm)
	Partially Supported	Supported	
12.5 to 14	225	150	100
15 to 34	150	100	100
35+	100	75	100

Note*: For Republic of Ireland a horizontal overlap of 225mm should be maintained for partially supported roofs up to a roof pitch of 22.5°. All other values in the table above are valid for ROI.

In the UK, given mild weather conditions, a maximum exposure period of 3 months should be adhered to for this underlay. In the winter months, or in cases of more extreme weather, this period should be reduced. Guidance on this is given by the BBA in an Information Bulletin on good site practice. A summary of this Bulletin is given later.

Eaves and roof edges: The underlay should be unrolled across the roof and draped a minimum of 150mm onto the proprietary eaves carrier. The eaves carrier needs to extend beyond the outer fascia board / tilting fillet edge to ensure effective drainage into the gutter – see figure 2.

Figure 1 - Unrolling





Figure 2 - Eaves Detail



Ridges: In duo-pitched roofs the underlay from one elevation should overlap the other by at least 150mm see figure 3. The underlay should be sealed around penetrations through the roof at the ridge to accommodate high level void ventilation. With mono-pitched roofs the underlay should be extended over the mono ridge by at least 100mm. It is recommended that the underlay be extended to provide protection to the ends of roof timbers.

Verges: At verges the underlay should be lapped over the outer walling (typically brickwork) by at least 50mm. Where the verge has a constructed overhang the underlay should be fixed to the outer rafter.

Abutments: The underlay should be returned up the abutment by at least 75mm below either a proprietary plastics or lead flashing – see figure 4.

Hips and valleys: Should be covered with a separate 600mm wide strip of Underlay.

Details: Ensure that when detailing around service penetrations, roof lights or chimneys the underlay is dressed a minimum of 100mm to the up-stand and is effectively sealed and weathered by an appropriate flashing.

Regulation requirements relating specifically to Southern Ireland*

Section 2 of Technical Guidance Document F, provides guidance on the requirements for ventilation of roofs. This specifies that:

All warm roofs should have a 50mm gap between the covering and underlay, which means that counter battens must be used.

There is no requirement for counter battens in cold roofs with most slating and tiling systems. If an airtight tiling system is used, BS 5250 requires battens over rigid sarking to facilitate ventilation of the batten space.

In Republic of Ireland in a non ventilated cold roof the use of a vapour control layer on the warm side of the insulation is essential. See section relating to installation in relevant Irish Agrément certificate identified on the roll insert.*

Health and Safety

Care should be taken in handling materials at height. In particular ensure that manual handling regulations are not exceeded. Sufficient edge protection, netting, appropriate scaffolding and hoisting are necessary to ensure the safe application of roofing underlays. Before work commences a method statement and risk assessment should be prepared.

Standards and Guidance

It is important to note that BS5250 requires that low resistance (LR) underlays be supported by third party certification, e.g. BBA, IAB, where they are to be used within an unventilated cold pitched roof.

BS 5534, British Standard Code of Practice for slating and tiling for pitched roofs and vertical cladding provides guidance and recommendations for the appropriate detailing and installation of underlays and roofing components, which should be followed when installing Dalpro® products

The British Board of Agrément has issued an Information Bulletin (No 2) relating to good site practice when using permeable roof tile underlays. This highlights :

An underlay is not a total waterproof barrier and, if used as a temporary waterproof covering, some rain penetration may occur.

In certain conditions, particularly if there is persistent heavy rainfall combined with subsequent severe freeze/thaw conditions, an underlay should not be exposed for more than a few days.

A full copy of this BBA Information Bulletin No 2 – Permeable Roof Tile Underlay Guide to Good Site Practice is available from the BBA website www.bbacerts.co.uk

For CE Accompanying Technical Document please contact your Distributor or visit www.donlow.co.uk
For information relating to these products in other languages please visit the Don & Low website www.donlow.co.uk

Don & Low believes that the information provided herein is accurate as at the date of publication. The information does not form part of any contract. Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

© Don & Low Limited, 2018. The intellectual property in the products is owned and protected by Don & Low or its licensors.

Figure 3 - Overlap Detail




Figure 4 - Abutment Detail

