

Daltex® RoofTX® is a range of low resistance vapour permeable, air barrier roofing underlay. Durable, flexible and lightweight, allowing for easy installation, all RoofTX® products offer temporary protection against wind driven rain, snow & dust.

- Conform to the construction Products Directive (EU Regulation no. 305/2011), underlays for discontinuous roofing (Annex ZA of EN 13859-1)
- Manufactured under control of an ISO 9001 quality management system

TEST	METHOD	Roofing and Walling						
Application		Roofing and Walling						
Function		Vapour permeable, air barrier LR roofing underlays and breather membranes for walling						
Brand Name		RoofTX® Optima	RoofTX® Prime	RoofTX® Ultra	RoofTX® 125	RoofTX® Maxi	RoofTX® Extra	
Product Code		FNS 92	FNS 102	FNS 112	FNS 125	FNS 170	FNE 230	
Fabric Weight (g/m ²)	EN 1849-2	92	102	112	125	170	230	
Tensile Strength (N)	EN 12311-1	MD	230	250	260	285	400	470
		CD	125	140	150	165	260	300
iab Certification		√	-	√	√	√	-	
SINTEF Certification		√	-	-	√	-	-	
BBA Certification		√	√	√	√	√	√	

MD = machine direction, CD = cross/transverse direction
LR = low resistance, VLR = very low resistance



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2018. The intellectual property in the products is owned and protected by Don & Low or its licensors.

Don & Low Ltd, Glamis Road, Forfar, Angus, DD8 1FR, Scotland, UK
t: +44(0) 1307 452200 f: +44(0) 1307 452201 e: enquiries@donlow.co.uk
w: www.donlow.co.uk

Issue 1
Jun 2018