

## Technical Information

Daltex<sup>®</sup> FrameTX<sup>®</sup> is a range of breather membrane for use in timber & steel frame constructions. Durable, flexible and lightweight allowing for easy installation, all FrameTX<sup>®</sup> products offer temporary protection against wind driven rain, snow and dust.

- Conform to the construction Products Directive (89/106/EEC), underlays for walls (Annex ZA of EN 13859-2)
- Manufactured under control of an ISO 9001 quality management system

TEST	METHOD			
Brand Name		FrameTX <sup>®*</sup>	FrameTX <sup>®</sup>	FrameTX <sup>®</sup>
			Maxi	Thermo*
Application		Walling - Housewrap, breather membrane		
Function		Vapour/air permeable spunbond	Vapour permeable/air barrier	Reflective breathable membrane
Product Code		FUV	FNS	RFL
Fabric Weight (g/m <sup>2</sup> )	EN 1849-2	100	102	134
Tensile Strength (N)	EN 12311-1	<b>MD</b> 240	250	230
		<b>CD</b> 180	140	160
BBA Certification		√	-	√

MD = machine direction, CD = cross/transverse direction  
LR = low resistance, VLR = very low resistance

\*Exclusively sold in the UK and Ireland by A Proctor Group: [www.proctorgroup.com](http://www.proctorgroup.com)



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2018. The intellectual property in the products is owned and protected by Don & Low or its licensors.