

Technical Datasheet

Daltex[®] PE is an ultra-soft and breathable polyethylene nonwoven with a suitably high resistance to abrasion.

Made from 100% recyclable polyethylene, Daltex[®] PE provides high strength properties suitable for a variety of medical applications, where softness and durability are important characteristics. Daltex[®] PE can be sewn, ultrasonically or heat welded, and is machine washable.

Daltex[®] PE is also gamma sterilisation stable.

TEST	METHOD	Daltex [®] PE					
Fabric Weight (g/m ²)	NWSP 130.1	20	40	60	80	100	
Tensile Strength (N)	NWSP 110.4	MD	17	30	45	80	100
		CD	10	18	25	45	75
Elongation (%)	NWSP 110.4	MD	190	200	220	280	300
		CD	200	210	230	290	310
Tear Strength (N)	ASTM D1424-07a	10	12	13	25	32	

MD = machine direction, CD = cross/transverse direction



Polyethylene is recyclable. Mechanical recycling is the primary option, depending of the requirements of the application and the intended article specification. Polyolefins are neither biodegradable nor compostable.

All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2019. The intellectual property in the products is owned and protected by Don & Low or its licensors.