

Technical Information

Breather membrane for timber and steel frame walls

Daltex[®] FrameTX[®] is a high performance air permeable breather membrane for use in timber & steel frame constructions. It is flexible & lightweight allowing for easy installation, and offers temporary protection for timber & steel frames against wind driven rain, snow & dust. Daltex[®] FrameTX[®] complies to the Construction Products Regulation (EU Regulation No. 305/2011), Underlay for walls (Annex ZA of EN 13859-2) and is manufactured under control of an ISO 9001 quality management system.


TEST	METHOD	FrameTX [®]	
Product Code		FU3 100	
Mass Per Unit Area (g/m ²)	EN 1849-2	100g/m ² (+/- 6 g/m ²)	
Reaction to Fire	EN 11925-2	Class E	
Water Vapour Resistance (Sd)	EN ISO 12572	0.006 m (+/- 0.002)	
Water Penetration	EN 13111	Before ageing	Class W2
		After ageing	Class W2
Tensile Strength (N/5cm)	EN 12311-1	Before ageing	MD 240 N (- 80 N) CD 180 N (- 60 N)
		After ageing	MD 200 N (-80 N) CD 150 N (- 60 N)
Elongation (%)	EN 12311-1	Before ageing	MD 85 % (-20%) CD 100 % (-20%)
		After ageing	MD 45 % (-20%) CD 60 % (-20%)
Tear Resistance (N)	EN 12310-1	MD 135 N (- 50 N) CD 145 N (- 50 N)	
Flexibility at low temperature	EN 1109	No cracking at minus 40° C	
Air Permeability (50Pa)	EN 12114	834 m ³ /m ² /hr	

Conditions applicable to the end use of the product

Rolls should be stored flat on a clean, level surface and kept under cover. Once the underlay is applied to the wall, the primary wall covering should be installed within one month.

Method of Installation

The membrane should be installed as detailed in the relevant national regulations. Any guidelines concerning installation that are supplied with the product should be consulted prior to laying. For general information –unroll the breather membrane and fit directly to the timber sheathing ensuring that the lower base timbers are covered. Lap the breather membrane by 100mm horizontally, 150mm vertically and external corners by 300mm. Upper layers should overlap lower to shed water away from the sheathing.



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2020. The intellectual property in the products is owned and protected by Don & Low or its licensors.