

Technical Datasheet

Meltblown PP is an electrostatically charged fabric designed for high bacterial filtration efficiency and with controlled air permeability.

Technical Details

	Test Method	M020A1WMS
Fabric weight (g/m ²)	NWSP 130.1	20
Air permeability (l/m ² /s)	NWSP 070.1	> 390
Particle Filtration Efficiency (%)	Paraffin Oil* 5.3 cm/s	> 79
Pressure Drop (Pa)	5.3 cm/s	< 28
Bacterial Filtration Efficiency (%)	EN 14683	> 98

* Measured with TSI 8130A – Count Median Diameter 0.16 µm & Mass Mean Diameter 0.4 µm (GSD ~2)



The above data is accumulated on flat sheet media.

Air permeability values are as produced and some compression of fabric may be observed when stored in roll form.

It is the responsibility of the customer to evaluate performance in a finished mask and to assess suitability for the intended end use.

All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2021. The intellectual property in the products is owned and protected by Don & Low or its licensors.