

Technical Datasheet

Lotrak[®] 30/30L is a biaxial geogrid designed to provide ground stabilisation and reinforcement. High strength, combined with low elongation provides effective reinforcement. The aperture design of the geogrid allows the aggregate to interlock and encourages load dispersal, particularly in applications such as unpaved roads.

TEST	STANDARD	Lotrak [®] 30/30L	
Tensile Strength (kN/m)	EN 10319	MD	30
		CD	30
Tensile Strength at 2% strain (%)	EN 10319	MD	10
		CD	9
Tensile Strength at 5% strain (%)	EN 10319	MD	21
		CD	20
Elongation at max. load (%)	EN 10319	MD	10
		CD	9
Grid Opening Size (mm)		60 x 60	
Effect of UV Light	The polypropylene (PP) used contains a UV inhibitor		
Roll Size (m)		Width	3.95
		Length	50



All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2022. The intellectual property in the products is owned and protected by Don & Low or its licensors.