

## Technical Information

### Vapour Control Layer

VapourTX<sup>®</sup> VCL146 is a high resistance vapour barrier for internal walls, ceilings and floors, specifically designed to reduce the transfer of water vapour through the structure when placed on the warm side of the insulation. VapourTX<sup>®</sup> VCL146 is a Type A vapour control layer tested to EN 13984 Flexible sheets for waterproofing - Plastics and rubber vapour control layers. VapourTX<sup>®</sup> VCL146 conforms to the Construction Products Regulation (EU Regulation No. 305/2011 as it has effect in the United Kingdom), vapour control layers (Annex ZA of EN 13984) and is manufactured under control of an ISO 9001 quality management system.

TEST	METHOD	VapourTX <sup>®</sup> VCL146					
Product Code		146 VCL					
Mass Per Unit Area (g/m <sup>2</sup> )	EN 1849-2	146 (+/- 10)					
Reaction to Fire	EN 11925-2	Class F					
Water Vapour Resistance (Sd)	EN 1931	15 m (+/- 2)					
Water Penetration	EN 1928	Class W1					
Tensile Strength (N/5cm)	EN 12311-1	<b>MD</b>	270	(-70)	<b>CD</b>	180	(-50)
Elongation (%)	EN 12311-1	<b>MD</b>	70	(+/-20)	<b>CD</b>	70	(+/-20)
Tear Resistance (N)	EN 12310-1	<b>MD</b>	190	(-40)	<b>CD</b>	170	(-40)

### Conditions applicable to the end use of the product

Rolls should be stored flat on a clean, level surface and kept under cover.

### Method of Installation

The vapour control layer should be installed as detailed in National Building Regulations. Any guidelines concerning installation that are supplied with the product should be consulted prior to laying. For general information – the vapour control layer should be positioned on the warm side of the thermal insulation.

In ceilings the product is placed between the underside of the rafters and the ceiling lining. In floors the product is placed on top of the structural decking or insulation (where present) and below any screed or sensitive floor coverings. Adjacent sheets should be lapped by 150mm and sealed with a suitable tape. Minimise penetrations caused by services and seal all joints.



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2024. The intellectual property in the products is owned and protected by Don & Low or its licensors.