



Muscle Up Your Roof.

Enhance your roof's performance and durability with **MultiTX**[®], the advanced, affordable and lightweight alternative to traditional bituminous based felts. **MultiTX**[®] blocks the flow of air and vapour like a boss and is now available in Plus (116 gsm), Pro (145 gsm), Maxi (190 gsm) and Solar variants. **BBA & NSAI Certified.**



The Ultimate
Roofing Barrier



High Resistance Air and Vapour Barrier Roofing Underlays for pitched roofs

MultiTX® is a family of high resistance air and vapour barrier roofing membranes, designed as a modern, cost effective and lightweight alternative to traditional bituminous based felts. The extended MultiTX® range consists of four distinct products, differing in weight and design: **MultiTX® Plus** (116g), **MultiTX® Pro** (146g) and **MultiTX® Maxi** (190g) are certified by the BBA for use in tiled and slat-

ed ventilated pitched roofs, in both supported and unsupported applications. **MultiTX® Solar**, which is designed specifically for integrated solar roofs, completes the family.

The MultiTX® range is also available in **MultiTX® Conseal versions**, boasting a factory applied, integral tape for easier installation and overlaps sealing.


Benefits

-  Protects against wind driven rain, snow and dust
-  Exceptional resistance to water penetration
-  Stabilised against UV degradation

Product	Weight	Wind Zone	Tensile Strength (N) after ageing	Tensile Strength (N) before ageing	Tear strength	Water penetration	Reaction to Fire
MultiTX® Plus	116 g/m ²	1-5 ¹	MD 220N/CD 140N	MD 260N/CD 170N	MD 140N/CD 130N	W1	CLASS F
MultiTX® Pro	145 g/m ²	1-5 ²	MD 200N/CD 150N	MD 290N/CD 220N	MD 230N/CD 250N	W1	CLASS F
MultiTX® Maxi	190 g/m ²	1-5	MD 280N/CD 210N	MD 400N/CD 300N	MD 300N/CD 400N	W1	CLASS F
MultiTX® Solar	145 g/m ²	1-5 ²	MD 200N/CD 150N	MD 290N/CD 220N	MD 230N/CD 250N	W1	CLASS F

MD = machine direction, CD = cross/transverse direction

- ¹ taping is required for wind zones 3-5
- ² taping is required for wind zones



All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, accepts or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2026. The intellectual property in the products is owned and protected by Don & Low or its licensors.



**Built on Tradition,
Driven by Innovation
Since 1792**

donlow.co.uk
Construction hotline
0808 169 4444

