

Datasheet

An extensive range of interlocking Tile Vents, suitable for six metric tile profiles (TLE, Flat, Double Roman, Double Pantile, Square Top and 15x9), with a 10,000mm² airflow and available in multiple colours. Can be laid down to 20° roof pitch.

Roof Ventilation	
Airflow	Space
5,000mm ²	2m Intervals at Ridge
10,000mm ²	1m Intervals at Eaves

Benefits


- ⊗ In-line and discrete look.
- ⊗ Can be used for high- and low-level roof space ventilation.
- ⊗ Can be used for mechanical extraction when fitted with a Flexipipe DL3FP.
- ⊗ Integral downpipe, no adaptor required.

Guidelines

To be fitted whilst laying the roof (can be retro fitted as well). The roof membrane needs to be cut to allow penetration into roof space. Cut an "X" into the membrane, folding back all 4 tabs, with the the top envelope tab folded back and fixed over the top batten. Can be used with Flexipipe DL3FP if connection required.

Specifications

	TLE	Flat	Double Pantile	Double Roman	Square Top	15x9	Flexipipe
Product Code	DL3TLEV	DL3FV	DL3DPV	DL3DRV	DL3STV	DL315X9V	DL3FP
Free Airflow	10,000mm ²	10,000mm ²	10,000mm ²	10,000mm ²	10,000mm ²	10,000mm ²	-
Weight	783g	811g	909g	893g	906g	854g	225g
Dimensions	418x330mm	418x330mm	418x330mm	418x330mm	418x330mm	328x226mm	110mm
Material	Acrylonitrile Styrene Acrylate (ASA) and Polypropylene (PP)						Polypropylene (PP)
Pcs / Carton	10	10	10	10	10	10	80
Cartons / Pallet	15	15	12	12	12	21	80
Manufacturing Process	Injection Moulding						-
Colours	Black, Grey, Brown, Red, Terracotta						Black
Regulations / Certifications	Compliant with all Relevant British Standards and Regulations						



Construction Technical Services

0808 169 4444

Don & Low Ltd, Glamis Road, Forfar, Angus, DD8 1FR, Scotland, UK
Tel: +44(0)1307 452200 Fax: +44 (0)1307 452201

Don & Low assumes no liability for written errors within this document.



All products are covered by 15 year Durability Warranty. Terms and conditions apply.



All plastic products are made in the UK.